

## Film Capacitors High Current, Wrap-and-Fill, Metallized Polypropylene



### FEATURES

- Wire or lug terminals
- High stability
- High ripple to 30 amperes
- Low inductance
- Low ESR


### PERFORMANCE CHARACTERISTICS

**Operating Temperature:** - 55 °C to + 105 °C  
**Capacitance Range:** 1.0 μF to 30.0 μF  
**Capacitance Tolerance:** ± 10 %, ± 5 %  
**DC Voltage Rating:** 100 WVDC to 400 WVDC  
**Equivalent Series Resistance:** 20 kHz to 100 kHz  
**Dissipation Factor:** 0.1 % maximum  
 Measured at 1000 Hz at + 25 °C  
 $\Delta V/\Delta T$ : 10 V/millisecond maximum  
**Voltage Test:** 200 % of rated voltage for 2 minutes  
**Insulation Resistance:** Measured at 100 WVDC after a 2 minute charge.  
 At + 25 °C: 200 000 Megohm - Microfarads, or 400 000 Megohm minimum  
**Vibration Test (Condition B):** No mechanical damage, short, open or intermittent circuits.

**DC Life Test:** 140 % of rated voltage for 1000 hours at + 105 °C. No visible damage. No open or short circuits.  
 Maximum  $\Delta$  CAP ± 1.0 %  
 Minimum IR = 50 % of initial limit  
 Maximum DF = 0.10 %  
**Humidity Test:** 95 % relative humidity at + 40 °C for 250 hours. No visible damage.  
 Maximum  $\Delta$  CAP ± 1.0 %  
 Minimum IR = 20 % of initial limit  
 Maximum DF = 0.12 %

### PHYSICAL CHARACTERISTICS

**Pull Test:**  
**Wire Leads:** - 5 pounds (2.3 kilograms) for one minute. No physical damage.  
**Terminal Lugs:** - 10 pounds (4.5 kilograms) for one minute. No physical damage.  
**Lead Bend:** After three complete consecutive bends, no damage.  
**Marking:** Sprague® trademark, type or part number, capacitance and voltage.



\* Leads to be within ± 0.062" [1.57 mm] of center line at egress but not less than 0.031" [0.79 mm] from edge (Terminal Style L only).



STANDARD RATINGS in inches [millimeters]											
CAPACITANCE ( $\mu$ F)	PART NUMBER**	CASE SIZE		ESR LIMIT (Milliohm) 20 kHz - 100 kHz	MAXIMUM RIPPLE CURRENT (Amps rms) at 20 kHz - 100 kHz Case Temperature at						
		D	L		+25 °C	+35 °C	+45 °C	+55 °C	+65 °C	+75 °C	+85 °C
<b>Terminal Style L - Units with Wire Leads</b>											
<b>100 WVDC</b>											
1.0*	735P105X9100L	0.531 [13.49]	0.750 [19.05]	15.0	9.2	8.5	7.8	7.0	6.0	4.9	4.5
2.0	735P205X9100L	0.596 [15.14]	0.938 [23.81]	12.0	10.8	10.0	9.1	8.2	7.0	5.8	5.3
3.0	735P305X9100L	0.717 [18.21]	0.938 [23.81]	11.0	12.1	11.2	10.3	9.2	8.0	6.5	5.9
5.0	735P505X9100L	0.733 [18.62]	1.250 [31.75]	10.0	13.8	12.7	11.6	10.4	9.0	7.4	6.7
10.0*	735P106X9100L	0.898 [22.81]	1.500 [38.10]	9.0	15.0	15.0	14.2	12.7	11.0	9.0	8.2
20.0	735P206X9100L	1.000 [25.40]	2.250 [57.15]	8.0	15.0	15.0	15.0	15.0	13.6	11.1	10.0
30.0	735P306X9100L	1.200 [30.48]	2.250 [57.15]	6.0	15.0	15.0	15.0	15.0	15.0	12.4	11.4
<b>200 WVDC</b>											
1.0*	735P105X9200L	0.512 [13.01]	1.250 [31.75]	20.0	7.3	7.3	7.3	7.3	7.2	5.9	5.4
2.0*	735P205X9200L	0.698 [17.73]	1.250 [31.75]	15.0	12.0	12.0	11.3	10.1	8.7	7.1	6.5
3.0	735P305X9200L	0.747 [18.97]	1.500 [38.10]	13.0	15.0	13.8	12.6	11.3	9.8	8.0	7.3
5.0*	735P505X9200L	0.862 [21.89]	1.750 [44.45]	11.0	15.0	15.0	14.7	13.1	11.4	9.3	8.5
10.0*	735P106X9200L	1.030 [26.16]	2.250 [57.15]	9.0	15.0	15.0	15.0	15.0	13.8	11.3	10.3
20.0	735P206X9200L	1.440 [36.58]	2.250 [57.15]	6.0	15.0	15.0	15.0	15.0	15.0	14.1	12.8
<b>400 WVDC</b>											
1.0*	735P105X9400L	0.713 [18.11]	1.500 [38.10]	19.0	9.5	9.5	9.5	9.5	9.5	7.8	7.1
2.0*	735P205X9400L	0.895 [22.73]	1.750 [44.45]	15.0	15.0	15.0	15.0	13.4	11.6	9.5	8.7
3.0*	735P305X9400L	1.086 [27.58]	1.750 [44.45]	12.0	15.0	15.0	15.0	15.0	13.1	10.7	9.8
5.0*	735P505X9400L	1.192 [30.28]	2.250 [57.15]	10.0	15.0	15.0	15.0	15.0	15.0	12.5	11.4
10.0*	735P106X9400L	1.668 [42.37]	2.250 [57.15]	6.0	15.0	15.0	15.0	15.0	15.0	15.0	14.1
<b>Terminal Style H - Units with Terminal Lugs</b>											
<b>100 WVDC</b>											
1.0	735P105X9100H	0.531 [13.49]	0.875 [22.23]	15.0	10.3	9.5	8.7	7.8	6.7	5.5	5.0
2.0	735P205X9100H	0.596 [15.14]	1.062 [26.97]	12.0	12.0	11.0	10.0	8.9	7.8	6.3	5.8
3.0	735P305X9100H	0.717 [18.21]	1.062 [26.97]	11.0	13.3	12.3	11.2	10.0	8.7	7.1	6.5
5.0	735P505X9100H	0.733 [18.62]	1.375 [34.93]	10.0	14.8	13.7	12.5	11.2	9.7	7.9	7.2
10.0	735P106X9100H	0.898 [22.81]	1.625 [41.28]	9.0	17.8	16.5	15.0	13.5	11.7	9.5	8.7
20.0	735P206X9100H	1.000 [25.40]	2.375 [60.33]	8.0	21.6	20.0	18.3	16.4	14.2	11.6	10.6
30.0	735P306X9100H	1.200 [30.48]	2.375 [60.33]	6.0	24.3	22.5	20.5	18.4	15.9	13.0	11.9
<b>200 WVDC</b>											
1.0	735P105X9200H	0.512 [13.00]	1.375 [34.93]	20.0	7.3	7.3	7.3	7.3	7.3	6.4	5.8
2.0	735P205X9200H	0.698 [17.73]	1.375 [34.93]	15.0	14.3	13.3	12.1	10.8	9.4	7.7	7.0
3.0	735P305X9200H	0.747 [18.97]	1.625 [41.28]	13.0	15.9	14.7	13.5	12.0	10.4	8.5	7.8
5.0	735P505X9200H	0.862 [21.89]	1.875 [47.63]	11.0	18.3	17.0	15.5	13.9	12.0	9.8	8.9
10.0	735P106X9200H	1.030 [26.16]	2.375 [60.33]	9.0	22.4	20.7	18.9	16.9	14.6	12.0	10.9
20.0	735P206X9200H	1.440 [36.58]	2.375 [60.33]	6.0	27.4	25.4	23.2	20.7	17.9	14.7	13.4
<b>400 WVDC</b>											
1.0	735P105X9400H	0.713 [18.11]	1.625 [41.28]	19.0	9.5	9.5	9.5	9.5	9.5	8.3	7.5
2.0	735P205X9400H	0.895 [22.73]	1.875 [47.63]	15.0	15.0	15.0	15.0	14.2	12.3	10.0	9.1
3.0	735P305X9400H	1.086 [27.58]	1.875 [47.63]	12.0	21.1	19.5	17.8	15.9	13.8	11.3	10.3
5.0	735P505X9400H	1.192 [30.28]	2.375 [60.33]	10.0	24.4	22.6	20.6	18.5	16.0	13.1	11.9
10.0	735P106X9400H	1.668 [42.37]	2.375 [60.33]	6.0	30.0	27.8	25.4	22.7	19.7	16.1	14.7

\* These ratings are stocked.

\*\* Part Numbers listed are for a capacitance tolerance of  $\pm 10\%$ . To specify  $\pm 5\%$  tolerance, change the "X9" in the Part Number to "X5".

ORDERING INFORMATION				
735P	105	X9	100	L
TYPE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING	TERMINAL STYLE
	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow.	X9 = $\pm 10\%$ X5 = $\pm 5\%$	This is expressed in volts.	L = Wire Leads H = Lugs



## Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.