





Material: COPPER Thickness: .045" / 1.14 mm

Basic Dimensions					Non-Insulated					Insulated (Red Vinyl) Insulation Diameter .265" / 6.73 mm					Insulated (Red Nylon) Insulation Diameter .315"/8.00 mm				
Stud Size	W In.	W mm	C In.	C mm	NIT Brazed	E In.	E mm	L In.	L mm	FIT	E In.	E mm	L In.	L mm	FIT Flared	Funnel FIT	E In.	E mm	L In.	L mm
8	.38	9.65	.39	9.91	R3499B	.72	18.29	.90	22.86	R3503B	1.04	26.42	1.23	31.24	R3503BF	R3503BFN	1.16	29.46	1.35	34.29
8	.47	11.94	.39	9.91	R2996B	.72	18.29	.95	24.13	R3030B	1.04	26.42	1.28	32.51	R3030BF	R3030BFN	1.16	29.46	1.39	35.31
10	.38	9.65	.39	9.91	R3500B	.72	18.29	.90	22.86	R3504B	1.04	26.42	1.23	31.24	R3504BF	R3504BFN	1.16	29.46	1.35	34.29
10	.47	11.94	.39	9.91	R3460B	.72	18.29	.95	24.13	R3031B	1.04	26.42	1.28	32.51	R3031BF	R3031BFN	1.16	29.46	1.39	35.31
10	.59	14.99	.57	14.48	R3445B	.91	23.11	1.20	30.48	R3027B	1.23	31.24	1.53	38.86	R3027BF	R3027BFN	1.34	34.04	1.63	41.40
1/4	.38	9.65	.39	9.91	R3501B	.72	18.29	.90	22.86	R3502B	1.04	26.42	1.23	31.24	R3502BF	R3502BFN	1.16	29.46	1.35	34.29
1/4	.47	11.94	.39	9.91	R3461B	.72	18.29	.95	24.13	R3032B	1.04	26.42	1.28	32.51	R3032BF	R3032BFN	1.16	29.46	1.39	35.31
1/4	.59	14.99	.57	14.48	R3444B	.91	23.11	1.20	30.48	R3028B	1.23	31.24	1.53	38.86	R3028BF	R3028BFN	1.34	34.04	1.63	41.40
5/16	.59	14.99	.57	14.48	R3462B	.91	23.11	1.20	30.48	R3033B	1.23	31.24	1.53	38.86	R3033BF	R3033BFN	1.34	34.04	1.63	41.40
3/8	.59	14.99	.57	14.48	R3463B	.91	23.11	1.20	30.48	R3034B	1.23	31.24	1.53	38.86	R3034BF	R3034BFN	1.34	34.04	1.63	41.40
3/8	.88	22.35	1.00	25.40	R3491B	1.33	33.78	1.76	44.70	R3043B	1.65	41.91	2.09	53.09	R3043BF	R3043BFN	1.77	44.96	2.21	56.13
1/2	.88	22.35	1.00	25.40	R3492B	1.33	33.78	1.76	44.70	R3042B	1.65	41.91	2.09	53.09	R3042BF	R3042BFN	1.77	44.96	2.21	56.13
1/2	1.25	31.75	1.00	25.40	R3494B	1.33	33.78	1.95	49.53	R3039B	1.65	41.91	2.28	57.91	R3039BF	R3039BFN	1.77	44.96	2.39	60.71
5/8	.88	22.35	1.00	25.40	R3493B	1.33	33.78	1.76	44.70	R3044B	1.65	41.91	2.09	53.09	R3044BF	R3044BFN	1.77	44.96	2.21	56.13
5/8	1.25	31.75	1.00	25.40	R3495B	1.33	33.78	1.95	49.53	R3040B	1.65	41.91	2.28	57.91	R3040BF	R3040BFN	1.77	44.96	2.39	60.71
3/4	1.25	31.75	1.00	25.40	R3496B	1.33	33.78	1.95	49.53	R3041B	1.65	41.91	2.28	57.91	R3041BF	R3041BFN	1.77	44.96	2.39	60.71
Hand Tool					H20					H20					H20	H20				

UL CSA

UL CSA N*

UL CSA

UL CSA

N* Items on this page are also available in nylon. To order, add **N** suffix to catalog number.
Example: BO110B**N**







Material: COPPER Thickness: .057" / 1.45 mm

Basic Dimensions					Non-Insulated					Insulated (Blue Vinyl) Insulation Diameter .350" /8.89 mm					Insulated (Blue Nylon) Insulation Diameter .430" / 10.92 mm				
Stud Size	W In.	W mm	C In.	C mm	NIT Brazed	E In.	E mm	L In.	L mm	FIT	E In.	E mm	L In.	L mm	FIT Flared	Funnel FIT	E In.	E mm	L In.	L mm
10	.47	11.94	.54	13.72	R64641B	.95	24.13	1.18	29.97	R4001B	1.38	35.05	1.62	41.15	R4001BF	R4001BFN	1.51	38.35	1.74	44.20
1/4	.47	11.94	.54	13.72	R64642B	.95	24.13	1.18	29.97	R4002B	1.38	35.05	1.62	41.15	R4002BF	R4002BFN	1.51	38.35	1.74	44.20
1/4	.63	16.00	.54	13.72	R64651B	.95	24.13	1.26	32.00	R4010B	1.38	35.05	1.70	43.18	R4010BF	R4010BFN	1.47	37.34	1.79	45.47
5/16	.63	16.00	.54	13.72	R64643B	.95	24.13	1.26	32.00	R4003B	1.38	35.05	1.70	43.18	R4003BF	R4003BFN	1.51	38.35	1.82	46.23
3/8	.63	16.00	.54	13.72	R64644B	.95	24.13	1.26	32.00	R4004B	1.38	35.05	1.70	43.18	R4004BF	R4004BFN	1.47	37.34	1.79	45.47
7/16	.63	16.00	.54	13.72	R64645B	.95	24.13	1.26	32.00	R4005B	1.38	35.05	1.70	43.18	R4005BF	R4005BFN	1.47	37.34	1.79	45.47
1/2	.88	22.35	1.00	25.40	R64654B	1.41	35.81	1.85	46.99	R4007B	1.85	46.99	2.28	57.91	R4007BF	R4007BFN	1.94	49.28	2.37	60.20
5/8	.88	22.35	1.00	25.40	R64655B	1.41	35.81	1.85	46.99	R4008B	1.85	46.99	2.28	57.91	R4008BF	R4008BFN	1.94	49.28	2.37	60.20
Hand Tool					H20					H20					H20	H20				

UL CSA

UL CSA N*

UL CSA

UL CSA

N* Items on this page are also available in nylon. To order, add **N** suffix to catalog number.
Example: R400B**N**

Most terminals available tape mounted.
Consult Electro-Term/Hollingsworth with your specifications.