

(2,54mm) .100"

SS, SD, ESD, ESS, HSS SERIES

PRECISION MACHINED SOCKET STRIPS

Mates with:
TS, TD, HTS, BBS,
BBD, BBL, BDL, BHS

SPECIFICATIONS

For complete specifications
see www.samtec.com?SS,
www.samtec.com?ESS,
www.samtec.com?SD or
www.samtec.com?ESD

SS, SD, ESS, ESD

Insulator Material:
Black G.F. Polyester

Contact:
BeCu

Shell:
Brass

except Style 5A
Phosphor Bronze

Current Rating:
1A

Plating:
Au over 50μ" (1,27μm) Ni or

Sn over 50μ" (1,27μm) Ni

Operating Temp Range:
-55°C to +125°C

Contact Resistance:
10 mΩ max

Lead Size Range:
(0,38mm to 0,56mm) .015" to
.022" DIA and most IC leads

Insertion Force:
(Single contact only)

Standard=

9oz (2,50N) avg.,

16oz (4,45N) max

Low Insertion Force=

2.5oz (0,70N) avg.,

5.5oz (1,53N) max

Withdrawal Force:
(Single contact only)

Standard=

2.5oz (0,70N) avg.,

1.5oz (0,42N) min

Low Insertion Force=

2.0oz (0,56N) avg.,

0.35oz (0,10N) min

Insertion Depth:
(-05, -1X & -21X, -5A)

(3,18mm) .125" to

(3,99mm) .157"

Insertion Depth: (-2, -22, -38)

(2,41mm) .095" to

(3,68mm) .145"

RoHS Compliant:
Yes

Lead-Free Solderable:
Wave only

SPECIFICATIONS

For complete specifications
see www.samtec.com?HSS

HSS

Same as SS except:

Insulator Material:
Black Liquid Crystal Polymer

Lead-Free Solderable:
Wave, or reflow with all Au



FILE NO. E111594

TYPE STRIP	1	NO. PINS PER ROW	PLATING OPTION	LEAD STYLE	OPTION	OTHER OPTION
------------	---	------------------	----------------	------------	--------	--------------

01 thru 32

= SS, ESS Series

01 thru 36

= HSS, SD & ESD Series

SS

= Standard Single Row Socket


HSS

= High Temp Single Row Socket

ESS

= Elevated Single Row Socket

Styles -5A & -05 socket
heads not countersunk.




SD

= Standard Double Row Socket

ESD

= Elevated Double Row Socket

Style -5A not available.
Styles -5A & -05 socket
heads not countersunk.



LIF= Low Insertion Force

Note:
Some lengths, styles and options are
non-standard, non-returnable.

-S

= 10μ" (0,25μm) Gold contact,
Tin shell
(Styles 2 & 22 only)

-T

= 30μ" (0,76μm) Gold contact,
Tin shell

-G


= 30μ" (0,76μm) Gold contact,
10μ" (0,25μm) Gold shell

-TT

= Tin contact and shell
(Styles 1, 2, 4, and 05
except LIF N/A)


-L = Locking Socket

Add -L suffix for locking
lead socket in end positions.
Requires Style -2 or -22 and
.035" ± .003 DIA board hole.



Requires -T Plating Option

-N
= Non
Flush




N/A Style -5A

ALSO AVAILABLE

Locking lead option on ESS
and ESD series. Contact Samtec.

-1A, -1B or -1C


For LIF specify -21A, -21B or -21C
(SS, HSS, SD)



LEAD STYLE	Y
-1A or -21A	(9,14) .360
-1B or -21B	(12,95) .510
-1C or -21C	(6,60) .260

-2, -22*, -5A, or -38*

*For LIF specify -22 or -38 (SS, HSS, SD)




LEAD STYLE	X DIA	Y	Z
-2 or -22	(0,51) .020	(3,18) .125	(7,62) .300
-38	(0,51) .020	(4,57) .180	(8,89) .350
-5A	(0,89) .035	(12,95) .510	(17,86) .703

Locking lead available. See OPTION.

-03, -04, -05

For LIF specify -23
(ESS, ESD)



LEAD STYLE	A	B	C
05	(17,86) .703	(13,46) .530	(4,39) .173
03 or 23	(11,51) .453	(7,62) .300	(3,89) .153
04	(14,05) .553	(10,16) .400	(3,89) .153

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC SILICON VALLEY • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292
SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766
SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683