



- [Edit Profile](#)
- [Edit Challenge](#)
- [Change Password](#)


| [Logout](#)
[My Parts \(0 items \)](#)

- [Products](#)
- [Industry Solutions](#)
- [CAREERS](#)
- [Resources](#)
- [Find Distributor](#)
- [Contact Molex](#)



Part Number: 67068-0110

Universal Serial Bus (USB), Shielded I/O, Type B Receptacle, Right Angle with Straight Tabs, Color Black, Gold (Au) Flash Plating, Tube Pack



Series image - Reference only

Status: Obsolete

Replacement: [Contact Molex](#)

Series: [67068](#)

Category: I/O Connectors

Mates With Part(s):

USB Type B Plug

Product Environmental Compliance

[EU ELV](#):Product not active

[EU RoHS](#):Product not active

[EU RoHS Phthalates](#):Product not active

[China RoHS](#):

[REACH SVHC](#):Product not active

[Low-Halogen Status](#):Product not active

Part Detail

General

Status	Obsolete
Category	I/O Connectors
Series	67068
Application	Wire-to-Board
Comments	Single
Component Type	Receptacle
Obsolete Date	2005/04/01
Product Name	USB
Type	B
UPC	800754774284

Physical

Boot Color	N/A
Circuits (Loaded)	4

Circuits (maximum)	4
Flammability	94V-0
Gender	Receptacle
Lock to Mating Part	Yes
Material - Plating Mating	Gold
Net Weight	3.462/g
Number of Rows	2
Orientation	Right Angle
PC Tail Length	2.80mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Packaging Type	Tube
Panel Mount	No
Pitch - Mating Interface	2.50mm
Pitch - Termination Interface	2.50mm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	1
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	0°C to +50°C
Termination Interface: Style	Through Hole
Waterproof / Dustproof	No
Wire Size AWG	N/A

Electrical**(Please review the Product Specification for specific details.)**

Current - Maximum per Contact	1.5A
Shield Type	Full Shield
Shielded	Yes
Voltage - Maximum	30V (RMS)

Agency Certification

Please find UL Certificates by searching the UL Database using the Molex Series Number. [Click here to visit the UL Database](#)

CSA	LR19980
UL	E29179

Solder Process Data**[Solderability Shelf Life Statement](#)**

Lead-free Process Capability	N/A
Process Temperature max. C	220

Material Info**Reference - Drawing Numbers**

Product Specification	PS-67998-0000
Sales Drawing	SDA-67068-****

Application Tooling

Tooling specifications and manuals are found by selecting the products below.

Crimp Height Specifications are then contained in the Application Tooling Specification document.

Previously Available Application Tooling

[Check our list of old tooling that used to be available for this part](#)

Products

- [Antennas](#)
- [Application Tooling](#)
- [Cable Assemblies](#)
- [Connected Lighting](#)
- [Connectors](#)
- [Copper Flex](#)
- [Electrical Products](#)
- [Industrial Automation](#)
- [Membrane Switches](#)
- [Optical Solutions](#)

Quick Links

- [Company Information](#)
- [Contact Molex](#)
- [Cross-Reference](#)
- [Koch Industries](#)
- [Industries](#)
- [Literature](#)
- [Molex Racing](#)
- [Press Room / Press Releases](#)
- [Product Index](#)

Resources

- [Supply Chain Transparency](#)
- [Compliance](#)
- [ecocare](#)
- [Feedback | Help](#)
- [Jobs](#)
- [Legal | Trademarks](#)
- [Mobile Site](#)
- [Supplier Portal](#)
- [Privacy Policy](#)
- [Tradeshows](#)

Stay Connected

- [PCB Assemblies](#)
- [Sitemap](#)

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.

© Copyright 2017