



a vital part of your world

Find Answers:

Saturday, 5 November, 2005

CATALOG

Cross Reference

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

RF Connectors

↳ BNC

AMP 227222-3 Active

(Corporate P/N: 227222-3)

Not ELV or RoHS Compliant

Search for Compliant (RoHS/ELV)

Alternates

CAD Geometry | Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ❖ General Info ❖ Sales Info ❖ Assembly Subcontractors 	<ul style="list-style-type: none"> ❖ Pricing & Availability 	<ul style="list-style-type: none"> ❖ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)

Searchable Features:

Brand:	AMP
Government/ Industry Qualification:	No
RoHS/ELV Compliance:	Not ELV/RoHS compliant
Lead Free Solder Processes:	Wave solder capable to 240° C, Wave solder capable to 265°C
Product Type:	Connector
Connector Type:	BNC
Gender:	Jack
Terminate To:	Printed Circuit Board
Stacked:	No
Number of Ports:	1

Other Properties:

Panel Attachment Style:	Rear Mount
Solder Terminal:	Without
Comment:	If an Insulating Bushing is required, see Part Number 330620. Lockwasher and Jam Nut must be ordered separately.

<u>PCB Mount Angle:</u>	Vertical
Surface Mount:	No
<u>Hardware Included:</u>	No
<u>Grade:</u>	Commercial
<u>Connector Impedance:</u>	50
<u>Panel Attachment:</u>	Yes
<u>Panel Attachment Method:</u>	Lockwasher and Nut
<u>Center Contact Material:</u>	Phosphor Bronze
<u>Center Contact Plating:</u>	Gold
<u>PCB Height (mm [in]):</u>	34.93 [1.375]
<u>PCB Retention Feature:</u>	With
<u>PCB Retention Method Feature:</u>	Mounting Post
<u>Mounting Post Style:</u>	Standard
<u>Mounting Post Length (Dim L) (mm [in]):</u>	3.48 [0.137]
<u>Body Material:</u>	VALOX
<u>Body Insulation:</u>	Without
<u>Sealed:</u>	No
<u>Isolated:</u>	No
<u>Dielectric Material:</u>	Polymethylpentene
<u>Color:</u>	White
<u>Polarized:</u>	No

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]