

Aluminum Capacitors + 85 °C, Miniature, Axial Lead



Fig.1 Component outline.

FEATURES

- High CV per case size
- Low cost
- Solvent resistant construction (through 100 WVDC)




QUICK REFERENCE DATA	
DESCRIPTION	VALUE
Nominal case size ØD x L in mm	0.197" x 0.472" [5.0 x 12.0] to 0.709" x 1.614" [18.0 x 41.0]
Operating temperature	- 40 °C to + 85 °C (- 25 °C to + 85 °C for 315 WVDC - 450 WVDC units)
Rated Capacitance range, C _R	0.47 µF to 10 000 µF
Tolerance on C _R	± 20 %
Rated voltage range, U _R	6.3 WVDC to 450 WVDC
Termination	2 axial leads
Life validation test at 85 °C	2000 hours: Δ CAP ≤ 20 % from initial measurement. Δ DF x 2 initial specified limit. Δ DCL ≤ initial specified limit.
Shelf life at 85 °C	1000 hours: Δ CAP ± 20 % from initial measurement. Δ DF 2 x initial specified limit. Δ DCL ≤ the initial specified limit.
DC leakage current	rated voltage for 1 minute for 6.3 WVDC to 100 WVDC units I < 0.03 CV or 4 µA (whichever is greater) rated voltage for 2 minute for 6.3 WVDC to 100 WVDC units I < 0.01 CV or 3 µA (whichever is greater) rated voltage for 1 minute for 160 WVDC to 450 WVDC units I < 0.1 CV + 40 µA and CV ≤ 1000 I < 0.04 CV + 100 µA and CV > 1000

RIPPLE CURRENT MULTIPLIERS						
TEMPERATURE						
Ambient Temperature			Multipliers			
≤ + 70 °C			1.27			
+ 85 °C			1.0			
FREQUENCY (Hz)/CAPACITANCE (µF)						
WVDC	Cap. (µF)	50 - 60	100 - 120	300 - 400	1kHz	≤ 10 kHz
6.3 - 100	0 - 47	0.75	1	1.35	1.57	2.00
	100 - 470	0.80	1	1.23	1.34	1.50
	1000 - 10000	0.85	1	1.10	1.13	1.15
160 - 450	1 - 100	0.80	1	1.25	1.40	1.60

LOW TEMPERATURE PERFORMANCE		
MAXIMUM IMPEDANCE RATIO Z ^(T) /Z ^(+20 °C) MAXIMUM AT 120 Hz		
Rated Voltage (WVDC)	Z - 25 °C/Z + 20 °C	Z - 40 °C/Z + 20 °C
6.3	4.0	10.0
10.0	3.0	8.0
16.0	2.0	6.0
25.0	2.0	4.0
35.0 - 100.0	2.0	3.0
160.0 - 250.0	4.0	12.0
315.0 - 350.0	6.0	-
400.0 - 450.0	15.0	-

DIMENSIONS in inches [millimeters]							
CASE CODE	NOMINAL CASE SIZE D x L	LEAD DIAMETER	TYPICAL WEIGHT (Grams)	CASE CODE	NOMINAL CASE SIZE D x L	LEAD DIAMETER	TYPICAL WEIGHT (Grams)
JL	0.197 x .472 [5.0 x 12.0]	0.024 [0.6]	0.56	NR	0.394 x 0.984 [10.0 x 25.0]	0.024 [0.6]	3.10
LL	0.248 x .472 [6.3 x 12.0]	0.024 [0.6]	0.74	PR	0.512 x 1.023 [13.0 x 26.0]	0.024 [0.6]	4.63
LM	0.248 x .472 [6.3 x 12.0]	0.024 [0.6]	0.91	PS	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	5.47
MM	0.315 x .630 [8.0 x 16.0]	0.024 [0.6]	1.00	QS	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	8.26
MN	0.315 x .787 [8.0 x 20.0]	0.024 [0.6]	1.70	QT	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	10.42
NP	0.394 x .827 [10.0 x 21.0]	0.024 [0.6]	2.32	RT	0.709 x 1.614 [18.0 x 41.0]	0.031 [0.8]	12.42

DIMENSIONS in inches [millimeters]



DIMENSIONS in inches [millimeters] AND PACKAGING QUANTITIES				
CASE CODE	TAPING CODE	SPECIFICATIONS		
		TAPE WIDTH $W \pm 0.059$ [1.5]	COMPONENT PITCH $P \pm 0.020$ [0.5]	QUANTITY PER REEL
JL	B	2.063 [52.4]	0.394 [10.0]	1600
LL	B	2.063 [52.4]	0.394 [10.0]	1300
LM	B	2.063 [52.4]	0.394 [10.0]	1300
MM	B	2.063 [52.4]	0.394 [10.0]	1000
MN	B	2.500 [63.5]	0.394 [10.0]	1000
NP	B	2.500 [63.5]	0.591 [15.0]	500
NP	C	2.874 [73.0]	0.591 [15.0]	500
NR	B	2.500 [63.5]	0.591 [15.0]	500
NR	C	2.874 [73.0]	0.591 [15.0]	500
PR	B	2.500 [63.5]	0.591 [15.0]	350
PR	C	2.874 [73.0]	0.591 [15.0]	350
PS	B	2.874 [73.0]	0.591 [15.0]	350

ELECTRICAL DATA	
SYMBOL	DESCRIPTION
μF	rated capacitance
$\pm \%$	$M = \pm 20 \%$
DC	voltage rating at 85 °C
JL	see dimensions in millimeters table
6	packaging code
A	termination

ORDERING EXAMPLE*

Electrolytic capacitor 500D series
 516D 107M 6R3 JL 6A
 6A = Bulk, Uncut leads.
 7B = tape and Reel. For case Codes JL, LL, LM, MM, MN, NP, NR, PR and PS only.
 7C = tape and Reel with 2.874" [73.0 mm] tape width (not stocked) For case Codes NP, NR and PR only.
 All items stating (Not stocked) are items that are not generally stocked unless a Purchase Order is placed. Lead time is 14 - 16 weeks for these items unless there is excess inventory.
 *Note: For lead (Pb)-free, add suffix E3 to part number.
 Example: 516D107M6R3JL6AE3

ELECTRICAL DATA AND ORDERING INFORMATION					
CAPACITANCE (μF)	PART NUMBER	NOMINAL CASE SIZE D x L	LEAD DIAMETER	Max. DF at + 20 °C	Max. RIPPLE at + 85 °C
6.3 WVDC at + 85 °C, SURGE = 8 V					
100	516D107M6R3JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.24	110
220	516D227M6R3LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.24	200
330	516D337M6R3LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.24	250

Aluminum Capacitors
+ 85 °C, Miniature, Axial Lead

Vishay Sprague

ELECTRICAL DATA AND ORDERING INFORMATION					
CAPACITANCE (μF)	PART NUMBER	NOMINAL CASE SIZE D x L	LEAD DIAMETER	Max. DF at + 20 °C	Max. RIPPLE at + 85 °C
6.3 WVDC at + 85 °C, SURGE = 8 V					
470	516D477M6R3MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.24	330
1000	516D108M6R3NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.24	600
2200	516D228M6R3PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.24	1020
3300	516D338M6R3PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.24	1200
4700	516D478M6R3QS6A	0.630 x 1.240 [16.0 x 31.5]	0.024 [0.6]	0.24	1500
6800	516D688M6R3QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.24	1840
10000	516D109M6R3QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.24	2260
10 WVDC at + 85 °C, SURGE = 13 V					
33	516D336M010JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.2	65
47	516D476M010JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.2	80
100	516D107M010LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.2	130
220	516D227M010LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.2	210
330	516D337M010MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	300
470	516D477M010MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	350
1000	516D108M010NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.2	640
2200	516D228M010PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.2	1090
3300	516D338M010PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.2	1390
4700	516D478M010QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.2	1730
6800	516D688M010QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.2	1930
10000	516D109M010RT6A	0.709 x 1.614 [18.0 x 41.0]	0.031 [0.8]	0.2	2350
16 WVDC at + 85 °C, SURGE = 20 V					
22	516D226M016JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.16	60
33	516D336M016JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.16	70
47	516D476M016JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.16	85
100.0*	516D107M016LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.16	160
220.0*	516D227M016MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.16	260
330	516D337M016MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.16	320
470.0*	516D477M016MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.16	430
1000	516D108M016NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.16	770
2200	516D228M016PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.16	1180
3300	516D338M016QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.16	1620
4700	516D478M016QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.16	1840
6800	516D688M016RT6A	0.709 x 1.614 [18.0 x 41.0]	0.031 [0.8]	0.16	2310
25 WVDC at + 85 °C, SURGE = 32 V					
10.0*	516D106M025JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.14	40
22.0*	516D226M025JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.14	65
33	516D336M025JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.14	80
47.0*	516D476M025LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.14	100
100.0*	516D107M025LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.14	170
220	516D227M025MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.14	280
330	516D337M025MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.14	380
470	516D477M025NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.14	510
1000	516D108M025PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.14	900

ELECTRICAL DATA AND ORDERING INFORMATION					
CAPACITANCE (μF)	PART NUMBER	NOMINAL CASE SIZE D x L	LEAD DIAMETER	Max. DF at + 20 °C	Max. RIPPLE at + 85 °C
25 WVDC at + 85 °C, SURGE = 32 V					
2200	516D228M025QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.14	1480
3300	516D338M025QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.14	1710
4700	516D478M025RT6A	0.709 x 1.614 [18.0 x 41.0]	0.031 [0.8]	0.14	2170
35 WVDC at + 85 °C, SURGE = 44 V					
10	516D106M035JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.12	45
22.0*	516D226M035JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.12	70
33	516D336M035LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.12	90
47	516D476M035LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.12	120
100	516D107M035MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.12	210
220	516D227M035MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.12	340
330	516D337M035NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.12	460
470	516D477M035NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.12	610
1000	516D108M035PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.12	1060
2200	516D228M035QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.12	1580
3300	516D338M035QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.12	2050
50 WVDC at + 85 °C, SURGE = 63 V					
0.47	516D474M050JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.1	5
1	516D105M050JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.1	10
2.2	516D225M050JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.1	23
3.3	516D335M050JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.1	28
4.7	516D475M050JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.1	34
10	516D106M050JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.1	50
22	516D226M050LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.1	85
33	516D336M050LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.1	110
47	516D476M050LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.1	130
100.0*	516D107M050MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.1	220
220	516D227M050NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.1	410
330	516D337M050NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.1	560
470	516D477M050PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.8]	0.1	730
1000	516D108M050QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.1	1260
2200	516D228M050RT6A	0.709 x 1.614 [18.0 x 41.0]	0.031 [0.8]	0.1	1920
63 WVDC at + 85 °C, SURGE = 79 V					
3.3	516D335M063JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	31
4.7	516D475M063JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	37
10.0*	516D106M063JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	55
22	516D226M063LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.08	90
33	516D336M063LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.08	120
47.0*	516D476M063MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.08	160
100	516D107M063MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.08	260
220	516D227M063NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.08	480
330	516D337M063PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.08	650
470	516D477M063PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.08	840
1000	516D108M063QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.08	1330

Aluminum Capacitors
+ 85 °C, Miniature, Axial Lead

Vishay Sprague

ELECTRICAL DATA AND ORDERING INFORMATION					
CAPACITANCE (μF)	PART NUMBER	NOMINAL CASE SIZE D x L	LEAD DIAMETER	Max. DF at + 20 °C	Max. RIPPLE at + 85 °C
100 WVDC at + 85 °C, SURGE = 125 V					
0.47	516D474M100JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	10
1	516D105M100JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	18
2.2	516D225M100JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	28
3.3	516D335M100JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	34
4.7	516D475M100JL6A	0.197 x 0.472 [5.0 x 12.0]	0.024 [0.6]	0.08	40
10	516D106M100LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.08	60
22	516D226M100MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.08	120
33	516D336M100MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.08	150
47	516D476M100MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.08	190
100	516D107M100NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.08	340
220	516D227M100PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.08	560
330	516D337M100PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.08	750
470	516D477M100QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.08	970
160 WVDC at + 85 °C, SURGE = 200 V					
1	516D105M160LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.2	13
2.2	516D225M160LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.2	23
3.3	516D335M160MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	33
4.7	516D475M160MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	39
10	516D106M160MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.2	60
22	516D226M160NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.2	120
33	516D336M160PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.2	170
47	516D476M160PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.2	230
100	516D107M160QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.2	430
200 WVDC at + 85 °C, SURGE = 250 V					
1	516D105M200LL6A	0.248 x 0.472 [6.3 x 12.0]	0.024 [0.6]	0.2	13
2.2	516D225M200LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.2	23
3.3	516D335M200MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	33
4.7	516D475M200MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	39
10	516D106M200NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.2	70
22	516D226M200PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.2	140
33	516D336M200PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.2	170
47	516D476M200PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.2	230
100	516D107M200QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.2	430
250 WVDC at + 85 °C, SURGE = 300 V					
1	516D105M250LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.2	14
2.2	516D225M250MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	27
3.3	516D335M250MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	33
4.7	516D475M250MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.2	45
10	516D106M250NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.2	70
22	516D226M250PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.2	140
33	516D336M250PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.2	190
47	516D476M250QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.2	260
100	516D107M250QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.2	430

ELECTRICAL DATA AND ORDERING INFORMATION					
CAPACITANCE (μF)	PART NUMBER	NOMINAL CASE SIZE D x L	LEAD DIAMETER	Max. DF at + 20 °C	Max. RIPPLE at + 85 °C
315 WVDC at + 85 °C, SURGE = 365 V					
1	516D105M315LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.2	14
2.2	516D225M315MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.2	27
3.3	516D335M315MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.2	36
4.7	516D475M315MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.2	45
10	516D106M315NR6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.2	80
22	516D226M315PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.2	150
33	516D336M315QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.2	210
47	516D476M315QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.2	260
350 WVDC at + 85 °C, SURGE = 400 V					
1	516D105M350LM6A	0.248 x 0.630 [6.3 x 16.0]	0.024 [0.6]	0.25	12
2.2	516D225M350MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.25	24
3.3	516D335M350MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.25	32
4.7	516D475M350NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.25	46
10	516D106M350PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.25	85
22	516D226M350PS6A	0.512 x 1.240 [13.0 x 31.5]	0.024 [0.6]	0.25	140
33	516D336M350QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.25	190
47	516D476M350QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.25	260
400 WVDC at + 85 °C, SURGE = 450 V					
1	516D105M400MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.25	14
2.2	516D225M400MN6A	0.315 x 0.787 [8.0 x 20.0]	0.024 [0.6]	0.25	28
3.3	516D335M400NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.25	38
4.7	516D475M400NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.25	46
10	516D106M400PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.25	85
22	516D226M400QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.25	150
33	516D336M400QT6A	0.630 x 1.633 [16.0 x 41.5]	0.031 [0.8]	0.25	210
47	516D476M400RT6A	0.709 x 1.614 [18.0 x 41.0]	0.031 [0.8]	0.25	290
450 WVDC at + 85 °C, SURGE = 500 V					
1	516D105M450MM6A	0.315 x 0.630 [8.0 x 16.0]	0.024 [0.6]	0.25	14
2.2	516D225M450MN6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.25	31
3.3	516D335M450NP6A	0.394 x 0.827 [10.0 x 21.0]	0.024 [0.6]	0.25	38
4.7	516D475M450NP6A	0.394 x 1.024 [10.0 x 26.0]	0.024 [0.6]	0.25	50
10	516D106M450PR6A	0.512 x 1.024 [13.0 x 26.0]	0.024 [0.6]	0.25	85
22	516D226M450QS6A	0.630 x 1.240 [16.0 x 31.5]	0.031 [0.8]	0.25	150
33	516D336M450QT6A	0.709 x 1.614 [18.0 x 41.0]	0.031 [0.8]	0.25	230

Note

* These values are normally stocked. Other ratings available as special order.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.