

Aluminum Capacitors Radial Long Life





Fig.1 Component outline.



FEATURES

- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case, all-insulated (light blue)
- Natural pitch 2.5 mm and 5 mm
- Charge and discharge proof
- Miniaturized, high CV-product per unit volume
- Long useful life: 2000 hours at 105 °C, high reliability
- Lead (Pb)-free versions are RoHS compliant.


RoHS*
COMPLIANT

APPLICATIONS

- Automotive, telecommunication, industrial and EDP
- Stand-by applications in audio and video equipment
- Coupling, decoupling, timing; smoothing, filtering and buffering in DC-DC converters
- Portable and mobile equipment (small size, low mass).

QUICK REFERENCE DATA	
DESCRIPTION	VALUE
Nominal Case sizes (∅D × L in mm)	5 × 11 and 8.2 × 11
Rated capacitance range, C _R	0.47 to 470 μF
Tolerance on C _R	±20%
Rated voltage range, U _R	6.3 to 100 V
Category temperature range	-55 to +105 °C
Endurance test at 105 °C	1500 hours
Endurance test at 85 °C	5000 hours
Useful life at 105 °C	2000 hours
Useful life at 40 °C, 1.3 × I _R applied	200000 hours
Shelf life at 0 V, 105 °C	1500 hours
Based on sectional specification	IEC 60384-4/EN130300
Climatic category IEC 60068	55/105/56

MARKING

The capacitors are marked (where possible) with the following information:

- Rated capacitance (in μF).
- Tolerance on rated capacitance, code letter in accordance with IEC 60062 (M for ±20%).
- Rated voltage (in V).
- Date code in accordance with IEC 60062.
- Code indicating factory of origin.
- Name of manufacturer.
- Minus-sign on top to identify the negative terminal.
- Series number (116).

SELECTION CHART FOR C _R , U _R AND RELEVANT NOMINAL CASE SIZES (∅D × L in mm)									
C _R (μF)	U _R (V)								
	6.3	10	16	25	35	40	50	63	100
0.47	-	-	-	-	-	-	5 × 11	-	-
1.0	-	-	-	-	-	-	5 × 11	-	-
1.5	-	-	-	-	-	-	5 × 11	-	-
2.2	-	-	-	-	-	-	5 × 11	-	8.2 × 11
3.3	-	-	-	-	-	-	5 × 11	-	-
4.7	-	-	-	-	-	-	5 × 11	-	8.2 × 11
6.8	-	-	-	-	-	-	5 × 11	-	-
10	-	-	-	-	-	-	5 × 11	8.2 × 11	8.2 × 11
15	-	-	-	-	-	-	5 × 11	-	-
22	-	-	-	-	-	-	5 × 11	8.2 × 11	-
33	-	-	-	-	5 × 11	5 × 11	8.2 × 11	-	-
47	-	-	-	5 × 11	-	-	8.2 × 11	-	-
68	-	-	5 × 11	-	-	-	8.2 × 11	-	-
100	-	5 × 11	-	-	8.2 × 11	8.2 × 11	-	-	-
150	5 × 11	-	-	8.2 × 11	-	-	-	-	-
220	-	-	8.2 × 11	-	-	-	-	-	-
330	-	8.2 × 11	-	-	-	-	-	-	-
470	8.2 × 11	-	-	-	-	-	-	-	-

* Pb containing terminations are not RoHS compliant, exemptions may apply

DIMENSIONS in millimeters **AND AVAILABLE FORMS**






Fig.2 Form CA: Long leads.




Case $\text{ØD} \times L = 5 \times 11$ and 8.2×11 mm.
Pitch $F = 5$ mm.

Fig.3 Form TFA: Taped in box (ammopack)



case $\text{ØD} \times L = 8.2 \times 11$ mm only

Fig.3 Form CB: Cut leads.



Case $\text{ØD} \times L = 5 \times 11$ mm only.
Pitch $F = 2.5$ mm.

Fig.4 Form TNA: Taped in box (ammopack)

Table 1

DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES								
NOMINAL CASE SIZE $\text{ØD} \times L$	CASE CODE	Ød	ØD_{max}	L_{max}	F	MASS (g)	PACKAGING QUANTITIES	
							FORM CA, CB	FORM TFA, TNA
5 × 11	11	0.5	5.5	12	2.5 ± 0.5	≈ 0.4	1000	2000
8.2 × 11	13	0.6	8.7	12	5.0 ± 0.5	≈ 1.1	1000	1000

Note

1. Tape dimension see section 'PACKAGING'.



ELECTRICAL DATA	
SYMBOL	DESCRIPTION
C _R	rated capacitance at 100 Hz, tolerance ±20%
I _R	rated RMS ripple current at 100 kHz, 105 °C
I _{L1}	max. leakage current after 1 minute at U _R
Tan δ	max. dissipation factor at 100 Hz
Z	max. impedance at 100 kHz and 20 °C

ORDERING EXAMPLE*

Electrolytic capacitor 116 series

220 μF/16 V; ±20%

Nominal case size: Ø8.2 × 11 mm; Form TFA

Catalog number: 2222 116 35221

* To ensure delivery of lead (Pb)-free parts during the transition period, please contact your Vishay sales agent.

Note

1. Unless otherwise specified, all electrical values in Table 2 apply at T_{amb} = 20 °C, P = 86 to 106 kPa, RH = 45 to 75%.


Table 2

ELECTRICAL DATA AND ORDERING INFORMATION														
U _R (V)	C _R 100 Hz (μF)	NOMINAL CASE SIZE ØD × L (mm)	I _R 100 kHz 105 °C (mA)	I _{L1} 1 min (μA)	Tan δ 100 Hz	Z 100 kHz (Ω)	CATALOG NUMBER 2222 116							
							BULK PACKAGING				TAPED AMMOPACK			
							LONG LEADS		CUT LEADS		FORM TFA		FORM TNA	
							FORM CA	F (mm)	FORM CB	F (mm)	FORM TFA	F (mm)	FORM TNA	F (mm)
6.3	150	5 × 11	130	8.7	0.25	1.3	53151	2.5	–	–	33151	5.0	73151	2.5
	470	8.2 × 11	300	21	0.25	0.45	53471	5.0	63471	5.0	33471	5.0	–	–
10	100	5 × 11	130	9	0.2	1.4	54101	2.5	–	–	34101	5.0	74101	2.5
	330	8.2 × 11	280	23	0.2	0.45	54331	5.0	64331	5.0	34331	5.0	–	–
16	68	5 × 11	130	9.5	0.16	1.5	55689	2.5	–	–	35689	5.0	75689	2.5
	220	8.2 × 11	280	24	0.16	0.5	55221	5.0	65221	5.0	35221	5.0	–	–
25	47	5 × 11	120	10	0.14	1.6	56479	2.5	–	–	36479	5.0	76479	2.5
	150	8.2 × 11	260	26	0.14	0.5	56151	5.0	66151	5.0	36151	5.0	–	–
35	33	5 × 11	110	9.9	0.12	1.7	50339	2.5	–	–	30339	5.0	70339	2.5
	100	8.2 × 11	240	24	0.12	0.55	50101	5.0	60101	5.0	30101	5.0	–	–
40	33	5 × 11	110	10.9	0.12	1.7	57339	2.5	–	–	37339	5.0	77339	2.5
	100	8.2 × 11	240	27	0.12	0.55	57101	5.0	67101	5.0	37101	5.0	–	–
50	0.47	5 × 11	30	3.1	0.09	10	51477	2.5	–	5.0	31477	5.0	71477	2.5
	1.0	5 × 11	40	3.3	0.09	6	51108	2.5	–	5.0	31108	5.0	71108	2.5
	1.5	5 × 11	50	3.5	0.09	4	51158	2.5	–	5.0	31158	5.0	71158	2.5
	2.2	5 × 11	60	3.7	0.09	3.5	51228	2.5	–	5.0	31228	5.0	71228	2.5
	3.3	5 × 11	65	4	0.09	3.1	51338	2.5	–	5.0	31338	5.0	71338	2.5
	4.7	5 × 11	70	4.4	0.09	2.8	51478	2.5	–	5.0	31478	5.0	71478	2.5
	6.8	5 × 11	75	5	0.09	2.5	51688	2.5	–	5.0	31688	5.0	71688	2.5
	10	5 × 11	80	6	0.09	2.2	51109	2.5	–	5.0	31109	5.0	71109	2.5
	10	8.2 × 11	160	6	0.05	1.0	90084	5.0	90085	5.0	90036	5.0	–	–
	15	5 × 11	90	7.5	0.09	2.0	51159	2.5	–	5.0	31159	5.0	71159	2.5
	22	5 × 11	110	9.6	0.09	1.9	51229	2.5	–	5.0	31229	5.0	71229	2.5
	22	8.2 × 11	190	9.6	0.06	0.9	90025	5.0	90086	5.0	90039	5.0	–	–
	33	8.2 × 11	190	13	0.09	0.77	51339	5.0	61339	5.0	31339	5.0	–	–
47	8.2 × 11	210	17	0.09	0.65	51479	5.0	61479	5.0	31479	5.0	–	–	
68	8.2 × 11	240	23	0.09	0.55	51689	5.0	61689	5.0	31689	5.0	–	–	
63	10	8.2 × 11	160	7	0.06	1.3	58109	5.0	68109	5.0	38109	5.0	–	–
	22	8.2 × 11	190	11	0.06	0.9	58229	5.0	68229	5.0	38229	5.0	–	–
100	2.2	8.2 × 11	60	4.3	0.06	4	59228	5.0	69228	5.0	39228	5.0	–	–
	4.7	8.2 × 11	75	5.8	0.07	3.5	59478	5.0	69478	5.0	39478	5.0	–	–
	10	8.2 × 11	100	9	0.08	3	59109	5.0	69109	5.0	39109	5.0	–	–




ADDITIONAL ELECTRICAL DATA		
PARAMETER	CONDITIONS	VALUE
Voltage		
Surge voltage		$U_s \leq 1.3 U_R$
Reverse voltage		$U_{rev} \leq 1 V$
Current		
Leakage current	after 1 minute at U_R	$I_{L1} \leq 0.006 C_R \times U_R + 3 \mu A$
	after 5 minutes at U_R	$I_{L5} \leq 0.001 C_R \times U_R + 3 \mu A$
Inductance		
Equivalent series inductance (ESL)	case $\varnothing D \times L = 5 \times 11 \text{ mm}$	typ. 13 nH
	case $\varnothing D \times L = 8.2 \times 11 \text{ mm}$	typ. 16 nH
Resistance		
Equivalent series resistance (ESR)	calculated from $\tan \delta_{max}$ and C_R (see Table 2)	$ESR = \tan \delta / 2\pi f C_R$

CAPACITANCE (C)



C_0 = capacitance at 20 °C, 100 Hz.


Fig.6 Typical multiplier of capacitance as a function of ambient temperature.



C_0 = capacitance at 20 °C, 100 Hz.

Fig.7 Typical multiplier of capacitance as a function of frequency.


IMPEDANCE (Z)



Case $\varnothing D \times L = 5 \times 11 \text{ mm}$.

$T_{amb} = 20^\circ C$.

Fig.8 Typical impedance as a function of frequency.



Case $\varnothing D \times L = 8.2 \times 11 \text{ mm}$.

$T_{amb} = 20^\circ C$.

Fig.9 Typical impedance as a function of frequency.

RIPPLE CURRENT AND USEFUL LIFE

I_A = actual ripple current at 100 kHz.
 I_R = rated ripple current at 100 kHz, 105 °C.
 (1) Useful life at 105 °C and I_R applied: 2000 hours.

Fig.10 Multiplier of useful life as a function of ambient temperature and ripple current load.




Table 3

MULTIPLIER OF RIPPLE CURRENT (I_R) AS A FUNCTION OF FREQUENCY			
FREQUENCY (Hz)	I_R MULTIPLIER		
	$U_R = 6.3$ to 10 V	$U_R = 16$ to 35 V	$U_R = 40$ to 100 V ($C_R \geq 10 \mu\text{F}$)
50	0.70	0.60	0.50
100	0.77	0.71	0.63
300	0.86	0.85	0.78
1000	0.92	0.93	0.88
3000	0.96	0.96	0.94
10 to 100 k	1.00	1.00	1.00

Table 4

TEST PROCEDURES AND REQUIREMENTS			
TEST		PROCEDURE (quick reference)	REQUIREMENTS
NAME OF TEST	REFERENCE		
Endurance	IEC 60384-4/ EN130300 subclause 4.13	$T_{\text{amb}} = 105$ °C; U_R applied; 1500 hours	$U_R \leq 6.3$ V; $\Delta C/C$: +15/-30% $U_R > 6.3$ V; $\Delta C/C$: $\pm 15\%$ $\tan \delta \leq 1.3 \times$ spec. limit $Z \leq 2 \times$ spec. limit $I_{L5} \leq$ spec. limit
Useful life	CECC 30301 subclause 1.8.1	$T_{\text{amb}} = 105$ °C; U_R and I_R applied; 2000 hours	$U_R \leq 6.3$ V; $\Delta C/C$: +45/-50% $U_R > 6.3$ V; $\Delta C/C$: $\pm 45\%$ $\tan \delta \leq 3 \times$ spec. limit $Z \leq 3 \times$ spec. limit $I_{L5} \leq$ spec. limit no short or open circuit total failure percentage: $\leq 1\%$
Shelf life (storage at high temperature)	IEC 60384-4/ EN130300 subclause 4.17	$T_{\text{amb}} = 105$ °C; no voltage applied; 1500 hours after test: U_R to be applied for 30 minutes, 24 to 48 hours before measurement	$\Delta C/C$, $\tan \delta$, Z : for requirements see 'Endurance test' above $I_{L5} \leq 2 \times$ spec. limit



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.