

Honeywell Sensing and Control

Search



392JB1K

(Home : Products : Sensors » Rotary Position Sensors » Conductive Plastic Potentiometers » 392)

Products

Controls Monitoring and Lighting (352)
 Machine Safety (1727)
 Sensors (5910)
 Switches (9774)
 Wireless (39)

Technology

Control and Instrumentation (1054)
 Electromechanical (9300)
 Microstructure (1495)
 Optical/Infrared (1042)
 Thick Film (1409)
 More...



Actual product appearance may vary.

392 Series Industrial Potentiometer, Conductive Plastic Element, PC Terminals, 0.5 W Power Rating, 1 kOhm Resistance Value

Customer Service
 Technical Support
 Global Sales & Service
 View Site Demo
 Site Comments?

[Distributor Inventory](#)

[Sales & Service](#)

- Overview
- Specs
- Documentation
- Application Notes

Description

The 392 Series is a 1/2 watt potentiometer with a conductive plastic element and a molded housing. It offers an internal shaft seal for moisture protection and PC style terminals.



VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™ find out more

white papers

Features

Features

Compact - 12,7 mm [0.5 in] diameter
 Conductive plastic element
 Linear taper
 Plastic bushing and shaft
 PC terminals

Potential Applications

Potential Applications

Manual controls
 Medical equipment
 Telecommunications

Meet Dr. Larry

Login to iCOM
 Login to Rep/AD Portal
 Login to Digital University

Product Specifications

Potentiometer Type	Industrial
Element Type	Conductive Plastic
Terminal	PC
Power Rating	0.5 W
Resistance Value	1 kOhm
Resistance Tolerance	± 10 %

HONEYWELL ANNOUNCE

Wireless Switches Offer Unlimited Benefit

Basic Switches Are Not Created Equal

Applying Precision Switches

Sensors for Medical Devices

New Ways to Measure Torque

Choosing Safety Switches

Specifying Hour Meters

[Click here to contact us](#)

Linearity	± 5 %
Bushing Thread	6,35 mm [0.25 in] x 32 NEF-2A
Bushing Length	6,35 mm [0.25 in]
Bushing Type	Standard
Shaft Diameter	3,18 mm [0.125 in]
Shaft Length	22,22 mm [0.875 in]
Shaft Ending	Slotted
Body	12.7 mm [0.5 in] diameter, ± 0.79 mm [0.031 in]
Electrical Taper	Linear
Operating Temperature	-40 °C to 120 °C [-40 °F to 248 °F]
Working Voltage (Max.)	350 V
Rotational Life	50000 cycles
Mechanical Rotation	295°
Availability	Global
Series Name	392
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

S ADDITION TO RELIALIGN™ RESIDENTIAL DOOR INTERLOCK SWITCHES THAT FEATURE RUGGED, PLASTIC HOUSING HONEYWELL'S XYR6000 WIRELESS POSITION SENSOR ENABLES MONITORING IN HAZARDOUS AREAS AND REMOTE LOCATIONS HONEYWELL RELEASES UNLIMITED POTENTIAL WITH NEW LIMITLESS™ WIRELESS SWITCHES



Dimensions



Accessory: Knobs

MICRO SWITCH Anniversary site



Product Range Guide



Documentation Page



Product Line Guide



Application Note Library

[Click here to download HI-Res image](#)