



DESIGNED FOR USE WITH .141 S/R CABLE	
CABLE ENTRY DIAMETER MINIMUM	
SLEEVE	.119
REAR DIELECTRIC	.050
CONTACT	.040

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
02 ₃	REVISED	6/28/96 6/12/96	[Signature]
B	PER EC 0U20-0692-00	21SEP01	C. Huang 21SEP01

CENTER CONTACT	BRASS PER ASTM-B-16 HALF HARD	GOLD PLATE PER MIL-G-45204
HOUSING	BRASS PER ASTM-B-16, HALF HARD	NICKEL PLATE PER QQ-N-290
SLEEVE	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
CLAMP NUT COUPLING NUT	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
RETAINING RING	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
RETAINING RING	PHOSPHOR BRONZE PER QQ-B-750, GRADE B2	N/A
GASKET	SILICONE RUBBER PER ZZ-R-765	N/A

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

FRAC. DEC. ANGLES
± 1/64 ±.005 ± 1°

DRAWN BY
B.B. DATE
9/22/67

CHECKED BY
B.W.C. 10/21/67

APPROVED BY
P.R.B. 3/7/71

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.

USE ASSY PROCEDURE

408-04910
(30-007)

NO. AP.

TITLE TYPE "N" SOLDER CLAMP ATTACHMENT			
SIZE B	CODE IDENT NO. 26805	3001-7841-00	REV 02 ₃
SCALE 4:1			SHEET 1 OF 1

.XXX = in
XX.X = mm

CUSTOMER DRAWING

AMP PART # 1057085-1
SHEET 1 OF 1 REV B