

AXIAL LEAD, METALLIZE POLYPROPYLENE FILM – OVAL

TS04D

FEATURES


- TS04D is constructed with metallized polyester film as medium and electricode, wrapped and sealed with flame-resistance plastic and epoxy resin, with high reliability, high-temperature-resistance, small volume, large capacity and good self-healing property.
- Mainly used in instruments and the DC & AC circuit of the household equipment and the fractional frequency circuit of acoustics system.

SPECIFICATIONS

OPERATING TEMPERATURE	-55°C TO + 100°C		
CAPACITANCE RANGE	0.1μF ~ 47μF		
CAPACITANCE TOLERANCE	J (±5%), K (±10%)		
RATED VOLTAGE	250V, 400V, 630V, 1000V, 1250V (DC)		
WITHSLAND VOLTAGE	1.7V _R 2s (1.5V _R 5s)		
DISSIPATION FACTOR	C ≤ 0.1μF	≤0.0015	10KHz
	0.1μF < C ≤ 1μF	≤0.0020	10KHz
	1μF < C ≤ 4.7μF	≤0.0030	10KHz
	C > 4.7μF	≤0.0015	1KHz
INSULATION RESISTANCE	C ≤ 0.33μF	≥50000MΩ	
	C > 0.33μF	≥1500S	



CAP	250VDC			400VDC			630VDC			1000VDC			1250VDC			
	W	T	H	W	T	H	W	T	H	W	T	H	W	T	H	
104	0.1	15	5	8	20	7	105	25	6.5	13	25	8	16	31	7.5	16
224	0.22	20	5	9	25	6.5	12.5	25	10	17	31	9.5	18.5	36	11	19.5
334	0.33	20	8.5	13	25	8.5	14	25	12.5	19	31	11.5	20	46	11	20
474	0.47	25	6.5	11	25	10	16.5	25	15	21	46	11.5	20	46	13.5	22.5
684	0.68	25	8	11	31	9.5	16	36	15	23	56	12.5	21	56	12	21
105	1.0	31	8.5	12	31	13	18	36	17	23	--	--	--	--	--	--
225	2.2	31	11	17.5	46	14.5	21	56	19.5	27.5	--	--	--	--	--	--
335	3.3	31	13.5	19.5	46	18	25	56	25	33	--	--	--	--	--	--
475	4.7	31	16.5	22.5	46	22	29	56	29.5	37	--	--	--	--	--	--
565	5.6	36	16	23	46	24	32	56	33	40.5	--	--	--	--	--	----
685	6.8	46	15.5	22	46	26	34	56	36	44	--	--	--	--	--	--
825	8.2	46	16.5	23.5	46	29	37	56	40	48	--	--	--	--	--	--
106	10.0	46	18.5	25	56	29	37	65	40	48	--	--	--	--	--	--
156	15.0	56	21	27.5	56	38	46	--	--	--	--	--	--	--	--	--
226	22.0	56	24.5	30	--	--	--	--	--	--	--	--	--	--	--	--
306	30.0	56	28	35	--	--	--	--	--	--	--	--	--	--	--	--
336	33.0	61	30	35.5	--	--	--	--	--	--	--	--	--	--	--	--
476	47.0	61	36.5	41	--	--	--	--	--	--	--	--	--	--	--	--



W < 20	d = 0.6mm ± 0.05
W ≥ 20	d = 0.8mm ± 0.05

Note: Specification are subject to change without notice. For more detail and update, please visit our website.